


Unique identification code of the product-type:	ROCKO MATT SILICONE
Intended application(s):	Sealant for facade elements for internal applications typ F-INT
Manufacturer:	WIM Sp. z o.o. ul. Wronia 61/63, 97-300 Piotrków Trybunalski www.wim-chb.pl
Constancy of performance assessment and verification system(s) for construction products defined under Attachment V:	System 4 for type tests System 4 for reaction to fire
Harmonized standards:	PN-EN 15651-1:2013 (EN 15651-1:2012) Sealants for non-structural use in joints in buildings and pedestrian walkways. Part 1: Sealants for facade elements
Declared Performances:	
Essential characteristics	Performance
Reaction to fire	Class F
Emission of chemicals hazardous to health and natural environment	See product data sheet
Water- and air tightness	
Runoff resistance	≤ 5 mm
Loss of volume	≤ 45%
Tensile properties (i.e. elongation): • at break at (23 °C (*)	≥ 25%
Durability	Meets requirements
(*) Conditioning: Method A; Glass substrate, without primer	
Product performance indicated above complies with the declared performance parameters. This declaration of performance has been drafted according to Regulation (EU) No. 305/2011 at the exclusive responsibility of the manufacturer indicated above.	
Signed on behalf of the manufacturer by: Paweł Lisiński w Piotrkowie Tryb. dn. 16.09.2022	
 WIM Sp. z o.o. Wiceprezes Zarządu Paweł Lisiński	