

Declaration of Performance (DoP)

Nr. 10011-MX-2014-10-10

1. Unique identification code of the product-type:

Extruded wood plastic composite decking type BS

2. Allowing identification of the construction product:

EAN-Code (s): 6428573981016

6428573981030

6428573981023

6428573982013

6428573982020

6428573982037

6428573989012

6428573989029

4741001220665

4741001220306

4741001200858

4741001220702

4741001220313

4741001220719

4741001220757

4741001220757

4741001200926

3. Intended uses of the construction product:

Products are used as indoor/outdoor decking. Product applications are specified in more details on the web site: www.maxfloor.fi

4. Name, registered trade name and contact address of the manufacturer:

Selectorpro Finland Oy (2549170-7)

Nuijamiestentie 5B, 2krs.

00400 HELSINKI, Finland

Tel. +358 45 146 4889

Email: maxfloor@selectorpro.fi

6. System of attestation of conformity:

AVCP 3


7. Declaration of performance concerning a construction product covered by a harmonized standard:

The Follow MaxFloor BS WPC products performance datas were tested in 2014 by SGC-CSTC Standards with CE Certificate.

9. Declared performance:

No	Test Item	Test Method	Result
1	Water Absorption	ASTM D1037-12 Section 23	0.23%
2	Moisture Content	ASTM D7031-04 Section 5.15 & ASTM D4442-07 Method B	0.2%
3	Abrasion Test	ASTM D7031-11 Section 5.17 & ASTM D4060-10 and client's requirement	97 mg
4	Specific Gravity	ASTM D7031-11 Section 5.14 and ASTM D792-08 Method B	1.3486
5	Mechanical Fastener Holding	ASTM D7032-10a Section 5.5 & ASTM D1761-12	2640 N
6	Oxygen Index	EN ISO4589- 1:1999 and EN ISO 4589-2:1999	25%
7	Linear Expansion with change in moisture content	ASTM D1037-12 Section 24	0.021%
8	Heat deflection temperature	ASTM D648-07 Method A	86.1°C
9	Tensile Strength	ASTM D638-10	15.7Mpa
10	Hardness	ASTM D2240-05(2010)	D/72/1
11	Grip Nail Strength	ASTM D7032-10a Section 5.5 & ASTM D1037-12 Section 14	558 N

Signed for and on behalf of the manufacturer by:
 Robbi Broända, CEO
 HELSINKI 10.10.2014



Signature