



SIMSON Prep K

PREPARATION AGENT

KEY BENEFITS

- Easy to use on several plastics
- Enhancing adhesion
- Easy to apply by brush

DESCRIPTION

Simson Prep K is a pretreatment to improve the adhesion of several specific Bostik products, based on Silyl Modified Polymer (SMP) and silicones, mainly on plastic substrates.

APPLICATION

- Pretreatment of plastics like hard and soft PVC (no PP, PE and PTFE).
- Pretreatment of ABS.

METHOD OF USE

Substrate: substrate needs to be dry, clean, and free of grease and dust. Keep container closed until using it.

Method of use: Keep container closed until moment of application. Open the container and puncture the foil. Do not use Simson Prep K from the container, but pour as much as one can work within 30 minutes in a separate can. Do not use remains of product after 30 minutes. Close container as soon as possible. Simson Prep K can be applied with a clean brush or with a cloth. Prep K is transparent, but can be discolor due to UV light, making it visible. If this is unwanted, it is necessary to use a masking tape. Do not pretreat a larger surface area than can be bonded within 6 hours. Do not touch treated surfaces, as this can affect adhesion negatively. Condensation may also affect adhesion negatively.

Strongly contaminated surfaces need to be cleaned first with for example Simson Cleaner 14 or Bostik Cleaner 1. Test if cleaner is affecting surface condition.

Note: Simson Prep K may attack the surface of some plastics. Please do a compatibility test before usage.

COVERAGE

The coverage of Prep K is approximately 4 to 6 m² per liter.

STORAGE STABILITY

Simson Prep K can be stored for 9 months in a closed (unopened) container in a dry place at temperatures between +5°C and +30°C.

TECHNICAL DATA

CHARACTERISTIC		VALUE
Dry content	[%]	12
Specific gravity	[g/ml]	0.9
Flash point		<0°C
Drying time 20°C/50%R.H.	[min]	30
Colour		Transparent
Packaging		500 ml tin
Application temperature		+5 - +30°C
Drying time	[min]	ca. 30

FURTHER INFORMATION

The following publication is available on request:

- Material Safety Data Sheets (MSDS)

The information given and recommendations made herein are based on Bostik's research only and are not guaranteed to be accurate. The performance of the product, its shelf life, and application characteristics will depend on many variables, including the kind of materials to which the product will be applied, the environment in which the product is stored or applied, and the equipment used for application. Any change in any of these variables can affect the product's performance. It is the buyer's obligation, prior to using the product, to test the suitability of the product for an intended use under the conditions that will exist at the time of the intended use. Bostik does not warrant the product's suitability for any particular application. The product is sold pursuant to Bostik's Terms and Conditions of Sale that accompanies the product at the time of sale. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute permission, inducement, or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

SMART HELP

Please contact your local representative

