

## Declaration of Performance

nr 167/DoP/29.01.2025

1. Unique identification code of the product:

Glulam 30

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to article 11(4):

**See delivery note**

3. Intended use or uses of the construction product in accordance with the applicable harmonised technical specification, as foreseen by manufacturer:

Buildings and bridges

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant article Article 11(5):

AS Liimpuit

Vabriku 44

63308 Põlva

Estonia

E-post: [info@polvaliimpuit.ee](mailto:info@polvaliimpuit.ee)

5. Where applicable, name and contact address of authorised representative whose mandate covers the tasks specified in article 12(2):

No representative

6. System or systems of assessment and verification of constancy of performance of the construction products assessed in annex V:

system1+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body MPA Stuttgart Otto Graf Institut, 0672, performed an initial test and an initial inspection of the factory concerning bonding strength, determination of product type and factory production control, continuous surveillance, assessment and evaluation of factory production control and issued a certificate of conformity no:

0672-CPD-I 14.21.17

8. In case of declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not Relevant

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
<b>Pressure strenght</b>	$f_{c,0,g,k} = 30 \text{ N/mm}^2$ $f_{c,90,g,k} = 2,5 \text{ N/mm}^2$	EN 14080:2013
<b>Flexure strenght</b>	$30 \text{ N/mm}^2$	
<b>Tensile strenght</b>	$f_{c,0,g,k} = 24 \text{ N/mm}^2$ $f_{c,90,g,k} = 0,5 \text{ N/mm}^2$	
<b>Shear</b>	$f_{v,g,k} = 3,5 \text{ N/mm}^2$	
<b>Bonding strenght</b>	According to EN 14080	
<b>Durability</b>	According EN 350-2	
Reaction to fire	According EN 13501-1	
Emission of hazardous substance	Class E1	

10. The performance of the product identified in ponts 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibilty of the manufacturer identified in point 4:

Põlva, 29.01.2025